



HOWO 380

The Toughest Ever

6x4 Prime Mover | 70,000 GCW | 380 HP



- Spacious Cabin
- Low Fuel Consumption
- Heavy Duty Axles
- Extra Loading Capacity



Dysin Automobiles Limited

www.dysin.com.pk

HOWO 380 (6x4) Prime Mover



Model

ماڈل

Model ZZ4257S3241



Cabin

کابین

HOWO 76 Long Cab, Hydraulically Damped Adjustable Driver's Seat, Safety Belts, Adjustable Steering Wheel, Air Horn, Fully Floating Suspension and Shock Absorber, Double Sleeper



Weight

وزن

Gross Combination Weight (kg) 60000
Chassis Weight (kg) 8800



Engine

انجن

Model WP10.380E22

Type Diesel, 4 Stroke In-Line, Direct Injection 6 Cylinder, Water Cooled, Turbo Charged with Intercooler

Max. Output (Hp@rpm) 380 @ 2200 rpm

Max. Torque (N.m@rpm) 1600 @ 1300-1500 rpm

Displacement (cc) 9726 (9.726 L)

Emission Standard Euro II



Transmission

ٹرانسمیشن

Model HW1970XST with Synchronizer

Type 9 Forward and 1 Reverse

Gear Ratio 3.28/ 7: 2.44/ 8: 1.8/ 9: 1.34/ 10: 1.00/ R1:14.01/ R 2.3.20

Final Ratio 4.8



Steering

سٹیرنگ

Type ZF8098 & ZF Steering Oil Pump, System Pressure 18.5Mpa, Power Steering



Clutch

کلیچ

Type WABCO Clutch Master Cylinder, Wheel Cylinder, Diaphragm Spring

Plate Diameter(mm) 430mm (17 inch)



Wheels & Tyres

ویلز اور ٹائرس

Tyre Size 11.00R20

No. of Tyres 10+1



Brake System

بریک

Service Brake ABS, Dual Circuit Compressed Air Brake, Rated Working Pressure is 810kpa, With The Exhaust Brake

Parking Brake Spring Energy, Breathe Brake on Rear Wheel

Auxiliary Brake Engine Exhaust Brake



Axle / Capacity kg

ایکسل

Front HF9 Front Axle, 7T Front Axle Heavyduty Drum Brake, Optional Disc

Rear MCX 13 Ton Single Reduction, Fully Floating Axleshafts



Suspension

سوسپنشن

Front Semi-Elliptic Leaf Springs and Stabilizers/9x13mm

Rear Semi-Elliptic Leaf Springs With Auxiliary Leaf Spring/ 3x22mm +9x20mm

Shock Absorbers Hydraulic Double Acting Telescopic in Front



Dimensions (mm)

ڈائمینشنز

Overall (L x W x H) 6800 x 2496 x 3790

Wheel Base (mm) 3200+1350

Min. Ground Clearance(mm) 314

Front Overhang(mm) 1500

Rear Overhang(mm) 725



Electrical System

الیکٹریکل سسٹم

Battery 24V, 165 Ah, Negative Grounded

Alternator 3-Phase

Starter 24V, 7.5kw



Performance

کارکردگی

Max Speed (km/h) 102

Max. Gradeability(%) 30

Fuel Tank Capacity(L) 400 (Aluminum)

ADDRESSES

Head Office

310-Fairy Meadows Lane, West Canal Bank Road, Lahore. Phone: 042 35292927 Fax: 042 35292842

Regional Office North

421/C, Avenue 1 Street 1, Westridge-1, Near Chur Chowk, Peshawar Road, Rawalpindi Phone: 051 5493604

Regional Office South

Karachi Market, Beside New Sabzi Mandi, Karachi Phone: 021 3454302 Fax: 021 34546427

Area Office South Punjab

Bahawalpur Bypass Road, Near Total Petrol Pump, Multan. Phone: 061 4482423



Exclusive After-Sale Services

☎ 0300-333-33-12



Note: Specifications Are Subject to Change Without Prior Notice.