



4x2 Rigid Truck | 18,500 GVW | 160 HP
HOMAN 160
Success Driven



- Premium Quality
- Low Fuel Consumption
- Strong Rigid Chassis
- Extra Loading Capacity



Dysin Automobiles Limited

www.dysin.com.pk

SINOTRUK 160 (4x2) Cargo Truck



Cargo Truck

کارجو ٹرک

Brand	SINOTRUK Homan
Emission	EURO II
Driving Type	4x2



Cabin

کابین

Type	2080 (Right Hand Drive)
Confguration	Seatbelt For Driver & Co-Driver
Seating Capacity	3 Seats+One Bunk



Weight

وزن

Curb Weight (KG)	4185
Gross Vehicle Weight (KG)	18,500



Engine

انجن

Model	YC4E160-33
Type	4 Cylinders In Line, 4 Strokes Direct Injection Diesel Engine, Water Cooling, Intercooler Turbocharged
Displacement (cc)	4.25L
Bore x Stroke	110x112
Max. Power (Hp@rpm)	160HP (118Kw) / 2600 Rpm
Max. Torque (N.m@rpm)	520 N.m/1300~1700 rpm



Transmission

ٹرانسمیشن

Model	DC6J70TC With Synchronizer
Numbers of Gears	6 forward Speeds, 1 Reverse Speeds
Gear Ratio	1: 6.54 / 2: 3.78 / 3: 2.168 / 4: 1.44 / 5: 1.00 / 6: 0.81 / R:6.53
Final Gear Ratio	5.285



Clutch

کلیچ

Type	Single Dry Plate Dry Coil-Spring Clutch
Plate Diameter(mm)	380 (15 Inches)



Wheels & Tyres

ویل / ٹائر

Number of Tyres	6+1
Tyre Size	10..00R20



Brake System

بریک

Type	Air Brake System, Air Pressure 0.8 Mpa
Service Brake	Dual Circuit Air Brake,
Parking Brake	Spring Energy, Compressed Air Operating on Real Wheels
Auxiliary Brake	Exhaust Valve Braking (EVb)



Axle / Capacity kg

ایکسل

Front	5500 Kg
Rear	13000 Kg



Steering

سٹیرنگ

Type	FN090ZY01, Power Steering
------	---------------------------



Dimensions (mm)

ڈائمینشنز

Overall Dimensions (L x W x H)	8300x2280x2750mm
Wheel Base (mm)	4700
Wheel Truck (Front/Rear)	1760/1750 mm
Overhang (Front/Rear) mm	1260/2115
Approach/Departure Angle	11x/29°



Electrical System

الیکٹریکل سسٹم

Working Voltage	24V, Negative Grounded
Starter	24V, 5.0Kw
Alternator	3-Phase 28V 55A
Battery Type	2x12V-105A.H



Chassis

چیمپرس

Main Stringer Section mm(Double Chassis)	255 x(6+5)
--	------------



Performance

کارکردگی

Max Speed (km/h)	125
Max.Gradeability(%)	23
Min Turning Radius(mm)	<9.4m
Min Ground Clearance(mm)	315
Fuel Tank Capacity(L)	200L

ADDRESSES

Head Office

310-Fairy Meadows
Lane, West Canal
Bank Road, Lahore.
Phone: 042 35292927
Fax: 042 35292842

Regional Office South

Plot # C-6 A/1, Estate
Avenue S.I.T.E. Karachi,
Adjacent KFC S.I.T.E., Karachi
Phone: 021 32554902
Fax: 021 32554902

Regional Office North

421/C, Avenue 1 Street 1,
Westridge-1, Near Chur
Chowk, Peshawar Road,
Rawalpindi
Phone: 051 5493604

Area Office South Punjab

Bahawalpur Bypass Road,
Near Total Petrol Pump,
Multan.
Phone: 061 4482423



Exclusive After-Sale Services



0300-333-33-12

Euro II

Note: Specifications Are Subject to Change Without Prior Notice.