



4x2 Prime Mover | 45.00 GCW | 240 HP
H5B 240
Power & Reliability



- Comfortable Cabin
- Fuel Efficient Engine
- Robust Transmission
- Extra Loading Capacity



Dysin Automobiles Limited

www.dysin.com.pk

H5B 240 (4x2) Prime Mover



Model

ماڈل

Model ZZ4188K3610C



Cabin

کیبن

HSF cab 4 point full-floating suspension, all-steel forward control, 70° hydraulically tiltable to the front, 3-arm wind screen wiper with 3 speeds, laminated wind screen with radio aerial, hydraulically damped adjustable driver's seat and rigid adjustable co-driver's seat, single sleeper, ventilating system, outer sun visor, adjustable roof flap, stereo radio/cassette recorder, safety belt and adjustable steering wheel, air conditioner, turn plate, air spoiler Option: fire extinguisher



Weight

وزن

Chassis Weight (KG) 5700
Gross Vehicle Weight (KG) 45000



Engine

انجن

Model YC6A240-33
Type Direct 4 Stroke In-Line Direct Injection
6 Cylinder Water Cooled, 12 Valve
Turbocharged With Intercooler
Max. Output (Hp@rpm) 240 @ 2500 rpm
Max. Torque (N.m@rpm) 630/1400 @ 1700
Displacement (cc) 7255 (7.2 Liter)
Bore x Stroke (mm) 108 x 132
Emission Standard Euro II



Transmission

ٹرانسمیشن

Model 8JS85TE
Type 8 Forward and 1 Reverse With Synchronizer



Steering

سٹیرنگ

Type D39, Power Steering



Exclusive After-Sale Services

0300-333-33-12



Clutch

کلیچ

Type Single dry Plate Dry Coil-Spring Clutch,
Hydraulically Operating With Air Assistance
Plate Diameter(mm) 432A (17 Inch)



Wheels & Tyres

ویلز / ٹائرز

Tyre Size 11.00R20
No. of Tyres 6+1



Brake System

بریک

Service Brake ABS, Dual Circuit Compressed
Air Brake, Rated Working Pressure
is 810kpa, With The Exhaust Brake
Parking Brake Spring Energy, Spring Energy
Breathe Brake on Rear Wheel
Auxiliary Brake Engine Exhaust Brake System (EVB)



Axle / Capacity kg

ایکسل

Front 5500 KG EQ 153 Heavy Duty, Forged
Ibeam Reverse Elliot Type
Rear 13 Ton, Punching Welding,
Single Reduction, Fully Floating Axle Shafts



Suspension

سپینشن

Front Semi-Elliptic Leaf Springs / Ordinary
before the Spring (12x13mm)
Rear Semi-Elliptic Leaf Springs With Auxiliary Leaf
Spring/Ordinary After Spring Type Engineering,
Reinforced After Spring, (10x12mm)
Shock Absorbers Hydraulic Double Acting
Telescopic in Front



Dimensions (mm)

ڈائمنشنز

Overall (L x W x H) 5915 x 2496 x 3050
Wheel Base (mm) 3600
Front Overhang(mm) 1320
Rear Overhang(mm) 815
Min. Ground Clearance(mm) 274



Performance

کارکردگی

Max Speed (km/h) 90
Max. Gradeability(%) >25
Min Turning Diameter(m) >8.5
Fuel Tank Capacity(L) 400(Aluminum)



Electrical System

الیکٹریکل سسٹم

Operation Voltage 2x12V, 165 Ah, Negative Grounded
Alternator 3-Phase
Starter 24V, 7.5kw

ADDRESSES

Head Office

310-Fairy Meadows
Lane, West Canal
Bank Road, Lahore.
Phone: 042 35292927
Fax: 042 35292842

Regional Office South

Karachi Market, Beside
New Sabzi Mandi, Karachi
Phone: 021 3454302
Fax: 021 34546427

Regional Office North

421/C, Avenue 1 Street 1,
Westridge-1, Near Chur
Chowk, Peshawar Road,
Rawalpindi
Phone: 051 5493604

Area Office South Punjab

Bahawalpur Bypass Road,
Near Total Petrol Pump,
Multan.
Phone: 061 4482423



Note: Specifications Are Subject to Change Without Prior Notice.