



6x2 Rigid Truck | 30000 GWW | 240 HP

H5B 240

Power & Reliability



- Comfortable Cabin
- Fuel Efficient Engine
- Robust Transmission
- Extra Loading Capacity



Dysin Automobiles Limited

www.dysin.com.pk

H5B 240 (6x2) Rigid Truck



Model

ماڈل

Model ZZ4188K3610C



Cabin

کیبن

H5F cab 4 point full-floating suspension, all-steel forward control, 70° hydraulically tiltable to the front, 3-arm wind screen wiper with 3 speeds, laminated wind screen with radio aerial, hydraulically damped adjustable driver's seat and rigid adjustable co-driver's seat, stereo sleeper, ventilating system, outer sun visor, adjustable roof flap, stereo radio/cassette recorder, safety belt and adjustable steering wheel, Option: Fire extinguisher air conditioner



Weight

وزن

Gross Vehicle Weight (KG) 30000
Chassis Weight (KG) 6700



Engine

انجن

Model YC6A240-33
Type Direct 4 Stroke In-Line Direct Injection
6 Cylinder Water Cooled, 12 Valve
Turbocharged With Intercooler
Max. Output (Hp@rpm) 240 @ 2500 rpm
Max. Torque (N.m@rpm) 630/1400 @ 1700
Displacement (cc) 7255 (7.2 Liter)
Bore x Stroke (mm) 108 x 132
Emission Standard Euro II



Transmission

ٹرانسمیشن

Model 8JS85TE
Type 8 Forward and 1 Reverse With Synchronizer



Steering

سٹیرنگ

Type D39, Power Steering



Exclusive After-Sale Services

0300-333-33-12



Clutch

کلیچ

Type Single dry Plate Dry Coil-Spring Clutch,
Hydraulically Operating With Air Assistance
Plate Diameter(mm) 432A (17 Inch)



Wheels & Tyres

ویلز / ٹائرز

Tyre Size 11.00R20
No. of Tyres 10+1



Brake System

بریک

Service Brake Dual Circuit Compressed
Air Brake, Rated Working Pressure
is 810kpa. With The Exhaust Brake
Parking Brake Spring Energy, Spring Energy
Breathe Brake on Rear Wheel
Auxiliary Brake Engine Exhaust Brake System (EVB)



Axle / Capacity kg

ایکسل

Front 5500 KG EQ 153 Heavy Duty, Forged
Ibeam Reverse Elliot Type
Rear 10 Ton x 2 457, Punching Welding,
Single Reduction, Fully Floating Axle Shafts



Suspension

سپینشن

Front Semi-Elliptic Leaf Springs / Ordinary
before the Spring (11x13mm)
Rear Semi-Elliptic Leaf Springs With Auxiliary Leaf
Spring/Ordinary After Spring Type Engineering,
Reinforced After Spring, (22x10mm)
Shock Absorbers Hydraulic Double Acting
Telescopic in Front



Dimensions (mm)

ڈائمینشنز

Overall (L x W x H) 8670x2496x3050mm
Wheel Base (mm) 4600+1350
Front Overhang(mm) 1320
Rear Overhang(mm) 2000
Min. Ground Clearance(mm) 274



Performance

کارکردگی

Max Speed (km/h) 90
Max. Gradeability(%) >25
Fuel Tank Capacity(L) 400(Aluminum)



Electrical System

ایلیکٹریکل سسٹم

Operation Voltage 2x12V, 165 Ah, Negative Grounded
Alternator 3-Phase
Starter 24V, 7.5kw

ADDRESSES

Head Office

310-Fairy Meadows
Lane, West Canal
Bank Road, Lahore.
Phone: 042 35292927
Fax: 042 35292842

Regional Office North

421/C, Avenue 1 Street 1,
Westridge-1, Near Chur
Chowk, Peshawar Road,
Rawalpindi
Phone: 051 5493604

Regional Office South

Karachi Market, Beside
New Sabzi Mandi, Karachi
Phone: 021 3454302
Fax: 021 34546427

Area Office South Punjab

Bahawalpur Bypass Road,
Near Total Petrol Pump,
Multan.
Phone: 061 4482423

Euro II

Note: Specifications Are Subject to Change Without Prior Notice.